Refrigeration - Refrigeration American Line - Refrigerated and freezer undercounter tables

### **Model AUTR-48**



Refrigeration - Refrigeration American Line - Refrigerated and freezer undercounter tables

### Model: AUTR-48

Reference	19032029
Nº doors	2
Nº shelves	2
Capacity (cubic foot)	11.8
HP	1/4
Working temperature (°F)	32° to 41 °F
Dimensions (mm)	1219 x 762 x 914
Dimensions (inches)	48" x 30" x 36"

# Model: Name: Project Name: Project Area: Project Item:

## **General characteristics**

#### REFRIGERATED AND FREEZER UNDERCOUNTER TABLES **AMERICAN LINE**


- All stainless steel interior and exterior construction for a cleaner and safer food environment.
- Coved corner floor to meet NSF requirements.
- Heavy duty stainless steel door with high impact ABS plastic interior door, step design for added insulation and protection of door gaskets.
- Durable stainless steel hinges.
- Recessed door handles.
- Self-closing door with 120° stay open feature for convenient loading and unloading of product.
- 36" high working height / 2-1/2" casters (opt.) for 34" high applications.
- CFC-Free polyurethane insulation, foamed in place for added strength and energy efficiency.

  Standard with 4" castors, front two with brakes.
- Self-contained system, no plumbing necessary.
- Easily removable door gaskets no tools necessary.
- Adjustable heavy duty epoxy coated wire shelves. REFRIGERATION MODELS SPECIFICATIONS:
- Electro-mechanic controller to keep food quality for longer period of time.
- Factory balanced refrigeration system, environmentally friendly R-134A.
- Maintain product temperatures from 32° to 41 °F, includes automatic defrost.
- FREEZER MODELS SPECIFICATIONS:
- New enhanced digital controller and display.
  Digital controller to keep food quality for longer period of time.
- Factory balanced refrigeration system, environmentally friendly
- Maintain product temperatures from 0 °F to -4 °F, includes automatic defrost.
- Front breathing refrigeration system for built-in applications.
- Volts 115V
- OPTIONS: Version 220V. 50/60 HZ





COLD TECHNICAL SPECIFICATIONS	
Climate class:	N
Compressor:	1/4
Condensation system:	Vent,
Gas type:	R-134a
GWP:	1430
High Side Pressure design:	300/20
Low side Pressure design:	132/9
Market:	Onnera Mexico
Numero compartimientos:	Uno
Refrigerant weigh Mex:	9,9/280
Refrigeration capacity Mex:	1730/508
SubFamilia:	ECO
Team:	Airtight
Termperature:	-2°C / 5°C
ELECTRICITY TECHNICAL SPECIFICATIONS	
Amperage (A):	5A
Electric frequency:	50/60Hz
Phases:	1P
Voltage:	115V
PRODUCT SPECIFICATIONS	
Gross Depth (mm):	840
Gross High (mm):	960
Gross weight (kg):	118
Gross Width (mm):	1300
Net Depth (mm):	762
Net High (mm):	914
Net Width (mm):	1219



Packaging dimensions: Height: 960 MM Depth: 840 MM Width: 1300 MM Gross weight: 118 KG