



Refrigeration - Refrigeration American Line - Refrigerated and freezer undercounter tables
Model AUTR-72

Model : _____
 Name : _____
 Project Name : _____

 Project Area : _____
 Project Item : _____



Refrigeration - Refrigeration American Line - Refrigerated and freezer undercounter tables

Model: AUTR-72

Reference	19032027
N° doors	3
N° shelves	6
Capacity (cubic foot)	18.2
HP	1/3
Working temperature (°F)	32° to 41 °F
Dimensions (mm)	1828 x 762 x 914
Dimensions (inches)	72" x 30" x 36"


General characteristics

REFRIGERATED AND FREEZER UNDERCOUNTER TABLES AMERICAN LINE

- All stainless steel interior and exterior construction for a cleaner and safer food environment.
- Covered corner floor to meet NSF requirements.
- Heavy duty stainless steel door with high impact ABS plastic interior door, step design for added insulation and protection of door gaskets.
- Durable stainless steel hinges.
- Recessed door handles.
- Self-closing door with 120° stay open feature for convenient loading and unloading of product.
- 36" high working height / 2-1/2" casters (opt.) for 34" high applications.
- CFC-Free polyurethane insulation, foamed in place for added strength and energy efficiency.
- Standard with 4" castors, front two with brakes.
- Self-contained system, no plumbing necessary.
- Easily removable door gaskets - no tools necessary.
- Adjustable heavy duty epoxy coated wire shelves.
- REFRIGERATION MODELS SPECIFICATIONS:
- Electro-mechanic controller to keep food quality for longer period of time.
- Factory balanced refrigeration system, environmentally friendly R-134A.
- Maintain product temperatures from 32° to 41 °F, includes automatic defrost.
- FREEZER MODELS SPECIFICATIONS:
- New enhanced digital controller and display.
- Digital controller to keep food quality for longer period of time.
- Factory balanced refrigeration system, environmentally friendly R-404 A.
- Maintain product temperatures from 0 °F to -4 °F, includes automatic defrost.
- Front breathing refrigeration system for built-in applications.
- Volts 115V
- OPTIONS: Version 220V. 50/60 HZ



COLD TECHNICAL SPECIFICATIONS	
Climate class:	N
Compressor:	1/4
Condensation system:	Vent,
Gas type:	R-134a
GWP:	1430
High Side Pressure design:	300/20
Low side Pressure design:	132/9
Market:	Onnera Mexico
Numero compartimientos:	Uno
Refrigerant weigh Mex:	9,9/280
Refrigeration capacity Mex:	1730/508
SubFamilia:	ECO
Team:	Airtight
Temperature:	-2°C / 5°C
ELECTRICITY TECHNICAL SPECIFICATIONS	
Amperage (A):	5A
Electric frequency:	50/60Hz
Phases:	1P
Voltage:	115V
PRODUCT SPECIFICATIONS	
Gross Depth (mm):	840
Gross High (mm):	960
Gross weight (kg):	148
Gross Width (mm):	1900
Net Depth (mm):	762
Net High (mm):	914
Net Width (mm):	1828



Packaging dimensions:
 Height: 960 MM
 Depth: 840 MM
 Width: 1900 MM
 Gross weight: 148 KG