DE

Refrigeration - Refrigeration American Line - Refrigerated and freezer undercounter tables Model AUTF-27



Refrigeration - Refrigeration American Line - Refrigerated and freezer undercounter tables

Model: AUTF-27

Reference	19032026
Nº doors	1
N⁰ shelves	1
Capacity (cubic foot)	6.1
HP	3/4
Working temperature (°F)	0 ° to -4 °F
Dimensions (mm)	685 x 762 x 914
Dimensions (inches)	27" x 30" x 36"

Model :	
Name :	
Project Name :	
Project Area :	
Project Item :	

General characteristics

REFRIGERATED AND FREEZER UNDERCOUNTER TABLES AMERICAN LINE

 All stainless steel interior and exterior construction for a cleaner and safer food environment.

- Coved corner floor to meet NSF requirements.
- Heavy duty stainless steel door with high impact ABS plastic interior door, step design for added insulation and protection of door gaskets.
- Durable stainless steel hinges.
- Recessed door handles.
- Self-closing door with 120° stay open feature for convenient loading and unloading of product.
- 36" high working height / 2-1/2" casters (opt.) for 34" high applications.
- CFC-Free polyurethane insulation, foamed in place for added strength and energy efficiency.
 Standard with 4" castors, front two with brakes.
- Self-contained system, no plumbing necessary.
- Easily removable door gaskets no tools necessary.
- Adjustable heavy duty epoxy coated wire shelves. REFRIGERATION MODELS SPECIFICATIONS:
- Electro-mechanic controller to keep food quality for longer
- period of time.
- Factory balanced refrigeration system, environmentally friendly R-134A.
- Maintain product temperatures from 32° to 41 °F, includes automatic defrost.
- FREEZER MODELS SPECIFICATIONS:
- New enhanced digital controller and display. Digital controller to keep food quality for longer period of time. Factory balanced refrigeration system, environmentally friendly
- R-404 A.
- Maintain product temperatures from 0 °F to -4 °F, includes automatic defrost.
- Front breathing refrigeration system for built-in applications. Volts 115V
- OPTIONS: Version 220V. 50/60 HZ

Refrigeration - Refrigeration American Line - Refrigerated and freezer undercounter tables **AUTF-27**

If any information is missing or you have found a mistake, please notify us at asber@asberprofessional.com


1

www.asberprofessional.com asber@asberprofessional.com

...asber



COLD TECHNICAL SPECIFICATIONS		
Climate class:	Ν	
Compressor:	3/4	
Condensation system:	Vent,	
Gas type:	R-404A	
GWP:	3922	
High Side Pressure design:	400/27	
Low side Pressure design:	250/17	
Market:	Onnera Mexico	
Numero compartimientos:	Uno	
Refrigerant weigh Mex:	9,5/270	
Refrigeration capacity Mex:	1580/460	
SubFamilia:	ECO	
Team:	Airtight	
Termperature:	-22°C /-14°C	
ELECTRICITY TECHNICAL SPECIFICATIONS		
Amperage (A):	8,5A	
Electric frequency:	60Hz	
Phases:	1P	
Voltage:	115V	
PRODUCT SPECIFICATIONS		
Gross Depth (mm):	840	
Gross High (mm):	1000	
Gross weight (kg):	78	
Gross Width (mm):	770	
Net Depth (mm):	762	
Net High (mm):	914	
Net Width (mm):	685	



Packaging dimensions: Height: 1000 MM Depth: 840 MM Width: 770 MM Gross weight: 78 KG

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing