



REFRIGERATED AND FREEZER UNDERCOUNTER TABLES AMERICAN LINE

- All stainless steel interior and exterior construction for a cleaner and safer food environment.
- Coved corner floor to meet NSF requirements.
- Heavy duty stainless steel door with high impact ABS plastic interior door, step design for added insulation and protection of door gaskets.
- Durable stainless steel hinges.
- Recessed door handles.
- Self-closing door with 120° stay open feature for convenient loading and unloading of product.
- 36" high working height / 2-1/2" casters (opt.) for 34" high applications.
- CFC-Free polyurethane insulation, foamed in place for added strength and energy efficiency.
- Standard with 4" castors, front two with brakes.
- Self-contained system, no plumbing necessary.
- Easily removable door gaskets - no tools necessary.
- Adjustable heavy duty epoxy coated wire shelves.
- REFRIGERATION MODELS SPECIFICATIONS:
- Electro-mechanic controller to keep food quality for longer period of time.
- Factory balanced refrigeration system, environmentally friendly R-134A.
- Maintain product temperatures from 32° to 41 °F, includes automatic defrost.
- FREEZER MODELS SPECIFICATIONS:
- New enhanced digital controller and display.
- Digital controller to keep food quality for longer period of time.
- Factory balanced refrigeration system, environmentally friendly R-404 A.
- Maintain product temperatures from 0 °F to -4 °F, includes automatic defrost.
- Front breathing refrigeration system for built-in applications.
- Volts 115V
- OPTIONS: Version 220V. 50/60 HZ

MODEL	REFERENCE	N° DOORS	N° SHELVES	CAPACITY (CUBIC FOOT)	HP	WORKING TEMPERATURE (°F)	DIMENSIONS (MM)	DIMENSIONS (INCHES)
AUTR-27	19032030	1	1	6.1	1/6	32° to 41 °F	685 x 762 x 914	27" x 30" x 36"
AUTR-48	19032029	2	2	11.8	1/4	32° to 41 °F	1219 x 762 x 914	48" x 30" x 36"
AUTR-60	19032028	2	2	15.0	1/3	32° to 41 °F	1524 x 762 x 914	60" x 30" x 36"
AUTR-72	19032027	3	6	18.2	1/3	32° to 41 °F	1828 x 762 x 914	72" x 30" x 36"
AUTF-27	19032026	1	1	6.1	3/4	0 ° to -4 °F	685 x 762 x 914	27" x 30" x 36"
AUTF-48	19032025	2	2	11.8	3/4	0 ° to -4 °F	1219 x 762 x 914	48" x 30" x 36"
AUTF-60	19032013	2	2	15.0	3/4	0 ° to -4 °F	1524 x 762 x 914	60" x 30" x 36"