



500

- Steady upper washing nozzles for more efficiency
- Electronic circuit with three washing programs
- Standard peristaltic rinse aid pump & detergent pump
- Stainless steel wash and rinse group
- Tank & boiler thermometer
- Self cleaning function and malfunction self diagnose
- Standard draining pump
- Thermo-protector feature



1510

- High Temp with Booster
- Capable of washing GN 1/1 pan
- Electronic circuit with three washing programs
- Standard peristaltic rinse aid pump & detergent pump
- Stainless steel washing nozzles
- Tank & boiler thermometer
- Self cleaning function and malfunction self diagnose
- Standard draining pump
- Thermo-protector feature

SPECIFICATIONS

	1510	500
Voltage	220V/60Hz/1ph	220V/60Hz/1ph
Power	1-1/2 hp	3/4 hp
Max Power	8.6 KW	3.6 to 6.6 KW
Type	Door Universal	Undercounter front loading
Basket Dimension	20" x 20"	20" x 20"
Door Clearance	15.75"	14.17"
Length of Cycle	60/ 120/ 180 sec **	60/ 120/ 180 sec **
Baskets/Hour	30	20/ 30/ 60 **
Glasses/Hour	1470	735/ 1470/ 2205 **
Dishes/Hour	540	270 - 540 - 810
Tank Capacity	15 Gallons	9.24 Gallons
Boiler Capacity	2 Gallons	1.58 Gallons
External Dimensions door close	29.52" x 34.64"x 54.7"	22.44" x 23.62"x 32.67"
External Dimensions door open	29.52" x 34.64"x 72"	22.44" x 37.87"x 32.67"
Net Weight	291 lbs	122 lbs
Shipping Dimensions	30" x 36" x 61"	24" x 28" x 40"
Shipping Weight	327 lbs	133 lbs

** (depends on the program selection).