

















FRG2VE

FRG4VE

FRG6VE

- All Stainless-Steel construction
- Sliding tempered glass doors
- Stainless steel V skewers, no hook required
- 2 Stainless steel grease drawer's collectors
- FRG4VE and FRG6VE 3" caster included
- FRG2VE and FRG8VE legs included
- Independent motor per skewers
- Motor rotation 2 rpm
- Capacity 5 chickens or 40 lbs. per spit
- Cooking time 50 to 60 min (calculates with 4 lbs. birds)

Ovens equipped only with V spit skewers

Easy, clean, no tools requires, secure, quick load and unload chickens

Installation Notes:



- At least a 5" clearance is needed on oven sides to right performance and use space.
- Ovens are top vent, operated under a hood or direct exhaust (where permitted)

	FRG2VE	SPECIFICATIONS FRG4VE	FRG6VE	FRG8VE
Chickens capacity	10	20	30	40
Voltage	110V/50-60hz/1ph	110V/50-60hz/1ph	110V/50-60hz/1ph	110V/50-60hz/1ph
Plug	Nema 15-5	Nema 15-5	Nema 15-5	Nema 15-5
Amps	1.2	1.8	3.6	4.8
Power (Btu)	30,000	60,000	90,000	120,000
External Dim WxDxH (inch)	24x46x31	24x46x58	24x46x65	24x46x70
Weight (lbs)	137	227	271	302
shipping Dim WxDxH	25x47x32	25x47x59	25x47x66	25×47×75
Shipping Weight (lbs)	167	267	271	302